

# NB2810-NLp-G

## Fahrzeug-Router mit 5G + LTE-A Pro + WLAN-ac + 2x GbE M12 + GNSS + E-Mark

Leistungsstarker und modularer Mobilfunk-Router für drahtlosen Internetzugang im Fahrzeug.



### Hauptmerkmale

<b>Mobilfunk</b>	1x 5G-NR, LTE-A Pro, UMTS 1x LTE, UMTS, GSM
<b>SIM</b>	4x Micro SIM
<b>WiFi / WLAN</b>	1x IEEE 802.11a/b/g/n/ac (Wi-Fi 5), 100 Clients im Access Point Mode
<b>Ethernet</b>	2x Gigabit Ethernet M12
<b>Speisung</b>	12 VDC bis 48 VDC, Zündungserkennung
<b>Ortung</b>	Multi-GNSS
<b>Betriebstemperatur</b>	-25 °C bis +70 °C
<b>Software</b>	Routing, Network Services, VPN, Firewall, Link Management, Supervisor, SDK, freie Updates
<b>Konformität</b>	CE (RED), Fahrzeug (UN ECE-R10, UN ECE-R118), ITxPT optional
<b>Modularität</b>	Erweiterungen auf Anfrage

### Produktbeschreibung

Der NB2800 bietet drahtlosen Internetzugang im Fahrzeug.

### Anwendungen

- Passagier-Infotainment
- Videüberwachung
- Fahrkartensysteme
- Intelligenter Verkehr
- Blaulichtorganisationen

### Spezifikation

<b>Mobile / Cellular</b>	<b>Standard</b>	<p>1x Multimode 5G-NR, LTE-A Pro, UMTS</p> <p><b>5G - NR</b> n1, n2, n3, n5, n7, n8, n12*, n20, n25, n28, n38, n40, n41, n48, n66, n71, n77, n78, n79</p> <p>2014/53/EU (RED): n1, n3, n7, n8, n20, n28, n38, n40, n77, n78</p> <p><b>4G - LTE-A Pro</b> B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B29DL, B30, B32, B34, B38, B39, B40, B41, B42, B43*, B46(LAA), B48(CRS), B66, B71</p> <p>2014/53/EU (RED): B1, B3, B7, B8, B20, B28, B38, B40</p> <p><b>3G - DC-HSPA+/UMTS</b> B1, B2, B3, B4, B5, B6, B8, B9, B19</p> <p>2014/53/EU (RED): B1 (2100), B3 (1800), B8 (900)</p> <p><b>5G - NR Modes</b> Sub-6 FDD and TDD</p> <p><b>LTE Category</b> Cat. 20 up to 7CA</p> <p><b>MIMO</b> 4x4 MIMO in 5G-NR support on n1, n2 n3, n7, n25, n38, n40, n41, n48, n66, n77, n78, n79 and LTE B1, B2, B3, B4, B7, B25, B30, B38, B39, B40, B41, B42, B43, B46, B48, B66</p> <p><b>Antenna ports</b> 4</p> <p><b>Power Class</b> 23dBm (Power Class 3)</p> <p><b>Data rate down / up (max)</b> up to 5.5 Gbps DL / 2.7 Gbps UL</p> <p><b>Operations Modes</b> 5G Core SA and NSA operations</p> <p><b>3GPP</b> 4G/5G Rel. 15, 3G HSPA+ Rel. 8</p> <p><b>FCC ID</b> RI7FN980</p> <p><b>Voice</b> -</p> <p><b>Region</b> Europe, Middle East and Africa (EMEA), North America (NA), Asia and Pacific (APAC)</p> <p>* future module firmware release</p> <p>1x Multimode LTE-A Pro, UMTS</p> <p><b>4G - LTE Advanced Pro</b> B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B29, B30, B38, B39, B40, B41, B42, B43, B48 (CBRS), B66, B71</p> <p>2014/53/EU (RED): B1, B3, B7, B8, B20, B28, B38, B40</p> <p><b>3G - DC-HSPA+/UMTS</b> B1, B2, B4, B5, B6, B8, B9, B19</p> <p>2014/53/EU (RED): B1, B8</p> <p><b>Category</b> LTE Cat 12</p> <p><b>Antenna ports</b> 2x2 MIMO</p> <p><b>Data rate down / up (max)</b> 600 Mbps / 150 Mbps</p> <p><b>3GPP</b> 4G Rel. 12, 3G DC-HSPA+</p> <p><b>Voice</b> -</p> <p><b>FCC ID</b> RI7LN920</p> <p><b>Region</b> Europe, Middle East and Africa (EMEA), North America (NA), Asia and Pacific (APAC)</p>
	<b>Region</b> <b>Connectors</b> <b>SIM</b>	<p>Europe</p> <p>6x FAKRA D-coded male</p> <p>4x Micro SIM - 3FF</p>
<b>Ethernet</b>	<b>Standard</b>	<p>2x Gigabit Ethernet</p> <p><b>Ethernet standard</b> 1000BASE-T, Auto MDIX</p> <p><b>Speed</b> 10/100/1000 Mbps</p>
	<b>Connector</b>	2x M12 X-coded female
<b>Positioning</b>	<b>Standard</b>	<p>1x Multi-GNSS</p> <p><b>Receiver</b> BeiDou, Galileo, GLONASS, GPS</p> <p>gpsOne Gen 9</p> <p><b>Antennas</b> Active or passive</p> <p><b>Tracking Sensitivity</b> Up to -161 dBm</p> <p><b>CEP (Circular Error Probability)</b> &lt; 2m (CEP 50), (Open sky conditions, Horizontal)</p> <p><b>Min update rate</b> 1Hz</p> <p><b>Services</b> Standalone</p>
	<b>Connector</b>	1x FAKRA C-coded male
<b>USB</b>	<b>Standard</b> <b>Connector</b>	<p>1x USB 3.0 Host</p> <p>1x Type A</p>
<b>Serial, Fieldbus</b>	<b>Protocol</b>  <b>Connector</b>	<p>1x RS-232</p> <p><b>Protocol</b> EIA-232</p> <p><b>Signals</b> TX, RX</p> <p><b>Signal level</b> High &gt; 5 VDC, low &lt; -5 VDC</p> <p><b>Bit rate</b> Up to 115 200 Bit/s</p> <p>1x Terminal block header 5 mm</p>
<b>System</b>	<b>Core</b> <b>Module Slots</b>	<p>1.3 GHz dual core, 1 GB RAM, 4 GB flash</p> <p>2x miniPCIe (PCIe + USB), 2x miniPCIe (USB)</p>

<b>Software</b>	<b>Features</b>	<p>NetModule Router Software</p> <p><b>Package</b> The standard software package includes an intuitive user interface, covering all modern routing protocols and enables efficient mass deployment.</p> <p><b>General</b> Fail-safe update (FOTA), upgrade via USB, HTTP(S), (S)FTP or TFTP, remote CLI &amp; WebGUI, RADIUS authentication, Simple Certificate Enrollment Protocol (SCEP), Hardware- und Software Watchdog</p> <p><b>Remote Management</b> Manage and monitor devices with SNMP V1/V2/V3, Netmodule vendor MIB, telnet, SSH, or HTTP/HTTPS</p> <p><b>Cellular Networking</b> Multi-SIM / eSIM support (optional license), multi-APN support, signal strength monitoring, dedicated bearers, CSFB/VoLTE calls (optional license)</p> <p><b>Wireless LAN</b> Access Point, Client Mode, Mesh Point or Dual Modes (Mesh Access Point / Access Point - Client), WLAN Pseudo-Bridge Client Mode: Multiple Client SSID Profile, Encryption: Open, WEP, WPA1/2/3-Personal, WPA1/2/3-Enterprise. Fast Roaming: Fast BSS Transition (802.11r), PreAuthentication, Protected Management Frames (802.11w) AP Mode: Multi-SSIDs (up to 8) Encryption: Open WPA1/2/3-Personal, WPA1/2/3-Enterprise Fast Roaming: Fast BSS Transition (802.11r), PreAuthentication, DFS support Protected Management Frames (802.11w) Client Tracking, Band Steering, Hide SSID broadcasting, Isolate Clients, Accounting, Short guard Intervall Mesh Mode (802.11s): Encryption: None, SAE. Gateway announcements</p> <p><b>Link Management</b> Link prioritization, link aggregation, load balancing, multipath-TCP, IP-passthrough, link supervision,</p> <p><b>Services</b> DHCP Client/Server, DNS Caching Server, Email, SMS Service, NTP Client/Server, SNMP Server, DynDNS, SSH Server, SNMP Agent, HTTP/HTTPS/FTP Server, IPv6 for WAN, 802.1x over Ethernet, MQTT Broker Voice Gateway (SIP, Call Routing, Audio with optional license) Coovachilli Hotspot</p> <p><b>Routing</b> Destination, policy, multipath, mobile-IP, OSPF, BGP, multicast, TCP-MSS clamping, bridging discovery protocols LLDAP, CDP, SONMP, EDP, FDP, IRDP, VRRP, STP/RSTP, VRRP, VLAN, PPPoE, VXLAN</p> <p><b>VPN</b> OpenVPN, IPsec (IKEv1 and IKEv2), PPTP, GRE, L2TP, CSD dial-in, Certificate revocation service</p> <p><b>Firewall</b> Stateful firewall, connection tracking, NAT, NAPT, masquerading, bridge filtering, Adress translation (based on SRC and DST ports)</p> <p><b>Encryption</b> supporting password protected PKCS12 files, integrated random certificate key generator, "Let's encrypt" certificate, ECC (Certificates with Elliptic Cryptography)</p> <p><b>Quality of Service</b> Diffserv, SFQ, HTB, Priority-based Queuing, Netflow (Softflow)</p> <p><b>Programmability</b> SDK</p> <p><b>Troubleshooting</b> Logging, Ping, Traceroute, Tcpdump, Speed-test</p>
	<b>Licenses</b>	<p>GNSS/GPS</p> <p><b>Services</b> Server with JSON-, NMEA stream</p>
<b>Power</b>	<b>Input Voltage</b>	<p>12, 24, 48 VDC</p> <p><b>Nominal voltages</b> 12, 24, 48 VDC</p> <p><b>Absolute voltages</b> 12 VDC to 48 VDC (-25 % / +25 %)</p> <p><b>Ignition sense</b> Input with delayed shutdown</p>
	<b>Ignition Sense</b>	Ja
	<b>Connector</b>	1x Terminal block header 5 mm
	<b>Consumption</b>	20 W (max)
<b>Mounting</b>		Bracket
<b>Dimensions</b>	<b>W x H x D</b>	Width 164/190 mm x height 58 mm x depth 139.5 mm
<b>Weight</b>		800 g
<b>Environment</b>	<b>Operating Temperature</b>	-25°C to +70°C
	<b>Ingress Protection Level</b>	IP40
<b>MTBF</b>		250'689 h / 28.6 years, according SN29500 at environmental temperature 40 °C
<b>Lieferumfang</b>		Device, General safety instructions, Terminal block
<b>Certifications</b>	<b>Compliance Domain</b>	CE according to 2014/53/EU (RED), Vehicle according to UNECE-R10, UNECE-R118 Vehicle
<b>Order Code</b>		NB2810-NLp-G