

# NB3800-2LpWacDa-GVi

## Bahn-Router mit 2xLTE-AP + WLANac + 32GB +GNSS +Virtualisierung+ EN50155

Leistungsstarker und modularer Mobilfunk-Router mit 5-Port Ethernet Switch für drahtlosen Internetzugang im Fahrzeug.



### Hauptmerkmale

<b>Mobilfunk</b>	2x LTE-A Pro, UMTS
<b>SIM</b>	4x Mini SIM
<b>WiFi / WLAN</b>	1x Dual-band IEEE 802.11a/b/g/n/ac (Wi-Fi 5), 100 Clients im Access Point Mode
<b>Ethernet</b>	2x Gigabit Ethernet, 3x Fast Ethernet
<b>Erweiterter Speicher</b>	32GB
<b>Speisung</b>	24 VDC bis 48 VDC
<b>Ortung</b>	Multi-GNSS
<b>Betriebstemperatur</b>	-25 °C bis +55 °C, EN 50155 class OT1/ST2
<b>Software</b>	Routing, Network Services, VPN, Firewall, Link Management, Supervisor, SDK, LXC Virtualisierung, freie Updates
<b>Konformität</b>	CE (RED), Bahn (EN50155, EN45545) , ITxPT optional
<b>Modularität</b>	Erweiterungen auf Anfrage

### Produktbeschreibung

Der leistungsstarke NB3800 ist mit seiner Ausstattung, seinen Bahnzulassungen und Schnittstellen zur Bordelektronik z.B. ideal für Fahrgastinformation, Passagier-WLAN oder auch Mining geeignet

### Anwendungen

- Mining
- Passagier-WLAN
- Passagier-Infotainment
- Videoüberwachung

### Spezifikation

<b>Mobile / Cellular</b>	<b>Standard</b>	2x Multimode LTE-A Pro, UMTS <b>4G - LTE Advanced Pro</b> B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B29, B30, B38, B39, B40, B41, B42, B43, B48 (CBRS), B66, B71 2014/53/EU (RED): B1, B3, B7, B8, B20, B28, B38, B40 <b>3G - DC-HSPA+/UMTS</b> B1, B2, B4, B5, B6, B8, B9, B19 2014/53/EU (RED): B1, B8 <b>Category</b> LTE Cat 12 <b>Antenna ports</b> 2x2 MIMO <b>Data rate down / up (max)</b> 600 Mbps / 150 Mbps <b>3GPP</b> 4G Rel. 12, 3G DC-HSPA+ <b>Voice</b> - <b>FCC ID</b> R17LN920 <b>Region</b> Europe, Middle East and Africa (EMEA), North America (NA), Asia and Pacific (APAC)
	<b>Region</b>	Europe
	<b>Connectors</b>	4x TNC female
	<b>SIM</b>	4x Mini SIM - 2FF
<b>WiFi / WLAN</b>	<b>Standard</b>	1x WLAN 2.4/5 GHz a/b/g/n/ac (Wi-Fi 5) <b>Wireless standard</b> IEEE 802.11a/b/g/n/ac (Wi-Fi 5) <b>Frequency</b> 2.4/5 GHz <b>Diversity</b> 2x2 MIMO <b>Data rate (max)</b> 300 Mbps (2.4 GHz) / 866 Mbps (5 GHz) <b>Modes</b> Client or access point (up to 100 clients) <b>FCC ID</b> TK4WLE600VX
	<b>Connector</b>	2x TNC female

<b>Ethernet</b>	<b>Standard</b>	2x Gigabit Ethernet <b>Ethernet standard</b> 1000BASE-T, Auto MDIX <b>Speed</b> 10/100/1000 Mbps
	<b>Connector</b>	3x Fast Ethernet <b>Ethernet standard</b> 100BASE-TX, Auto MDIX <b>Speed</b> 10/100 Mbps 2x M12 X-coded female, 3x M12 D-coded female
<b>Positioning</b>	<b>Standard</b>	1x Multi-GNSS <b>Receiver</b> BeiDou, Galileo, GLONASS, GPS gpsOne Gen 9 <b>Antennas</b> Active or passive <b>Tracking Sensitivity</b> Up to -158 dBm <b>CEP (Circular Error Probability)</b> < 2m (CEP 50), (Open sky conditions, Horizontal) <b>Services</b> Standalone
	<b>Connector</b>	1x TNC female
<b>USB</b>	<b>Standard</b>	1x USB 2.0 Host
	<b>Connector</b>	1x Type A
<b>Serial, Fieldbus</b>	<b>Protocol</b>	1x RS-232 <b>Protocol</b> EIA-232 <b>Signals</b> TX, RX <b>Signal level</b> High > 5 VDC, low < -5 VDC <b>Bit rate</b> Up to 115 200 Bit/s
	<b>Connector</b>	1x M12 A-coded female
<b>Extended Storage</b>		32 GB SSD <b>Capacity</b> 32 GB <b>Technology</b> SSD <b>Data</b> Application data such as logs, media content, ...
<b>System</b>	<b>Core</b> <b>Module Slots</b>	1.3 GHz dual core, 1 GB RAM, 4 GB flash 2x miniPCle (PCle + USB), 4x miniPCle (USB)
<b>Software</b>	<b>Features</b>	NetModule Router Software <b>Package</b> The standard software package includes an intuitive user interface, covering all modern routing protocols and enables efficient mass deployment. <b>General</b> Fail-safe update (FOTA), upgrade via USB, HTTP(S), (S)FTP or TFTP, remote CLI & WebGUI, RADIUS authentication, Simple Certificate Enrollment Protocol (SCEP), Hardware- und Software Watchdog <b>Remote Management</b> Manage and monitor devices with SNMP V1/V2/V3, Netmodule vendor MIB, telnet, SSH, or HTTP/HTTPS <b>Cellular Networking</b> Multi-SIM / eSIM support (optional license), multi-APN support, signal strength monitoring, dedicated bearers, CSFB/VoLTE calls (optional license) <b>Wireless LAN</b> Access Point, Client Mode, Mesh Point or Dual Modes (Mesh Access Point / Access Point - Client), WLAN Pseudo-Bridge Client Mode: Multiple Client SSID Profile, Encryption: Open, WEP, WPA1/2/3-Personal, WPA1/2/3-Enterprise. Fast Roaming: Fast BSS Transition (802.11r), PreAuthentication, Protected Management Frames (802.11w) AP Mode: Multi-SSIDs (up to 8) Encryption: Open WPA1/2/3-Personal, WPA1/2/3-Enterprise Fast Roaming: Fast BSS Transition (802.11r), PreAuthentication, DFS support Protected Management Frames (802.11w) Client Tracking, Band Steering, Hide SSID broadcasting, Isolate Clients, Accounting, Short guard Intervall Mesh Mode (802.11s): Encryption: None, SAE. Gateway announcements <b>Link Management</b> Link prioritization, link aggregation, load balancing, multipath-TCP, IP-passthrough, link supervision, <b>Services</b> DHCP Client/Server, DNS Caching Server, Email, SMS Service, NTP Client/Server, SMTP Server, DynDNS, SSH Server, SNMP Agent, HTTP/HTTPS/FTP Server, IPv6 for WAN, 802.1x over Ethernet, MQTT Broker Voice Gateway (SIP, Call Routing, Audio with optional license) Coovachilli Hotspot <b>Routing</b> Destination, policy, multipath, mobile-IP, OSPF, BGP, multicast, TCP-MSS clamping, bridging discovery protocols LLDP, CDP, SONMP, EDP, FDP, IRDP, VRRP, STP/RSTP, VRRP, VLAN, PPPoE, VXLAN <b>VPN</b> OpenVPN, IPsec (IKEv1 and IKEv2), PPTP, GRE, L2TP, CSD dial-in, Certificate revocation service <b>Firewall</b> Stateful firewall, connection tracking, NAT, NAT, masquerading, bridge filtering, Adress translation (based on SRC and DST ports) <b>Encryption</b> supporting password protected PKCS12 files, integrated random certificate key generator, "Let's encrypt" certificate, ECC (Certificates with Elliptic Cryptography) <b>Quality of Service</b> Diffserv, SFQ, HTB, Priority-based Queuing, Netflow (Softflow) <b>Programmability</b> SDK
	<b>Licenses</b>	<b>Troubleshooting</b> Logging, Ping, Traceroute, Tcpdump, Speed-test GNSS/GPS, <b>Services</b> Server with JSON-, NMEA stream LXC virtualization <b>Enabled service</b> Linux Container (LXC) environment to integrate customer specific applications, isolated from the router functionalities

<b>Power</b>	<b>Input Voltage</b>	24, 48 VDC <b>Nominal voltages</b> 24, 48 VDC <b>Absolute voltages</b> 24 VDC to 48 VDC (-30 % / +30 %) <b>Galvanic isolation</b> 1500 VDC <b>Standard</b> EN 50155 class S2/C1
	<b>Connector</b>	1x M12 A-coded male
	<b>Consumption</b>	25 W (max)
<b>Dimensions</b>	<b>W x H x D</b>	Width 167/190 mm x height 121.1 mm x depth 106.5 mm
<b>Weight</b>		2000 g
<b>Environment</b>	<b>Operating Temperature</b>	-25°C to +55°C
	<b>Ingress Protection Level</b>	IP40
<b>MTBF</b>		158'399 h / 18.08 years, according SN29500 at environmental temperature 40 °C
<b>Certifications</b>	<b>Compliance Domain</b>	CE according to 2014/53/EU (RED), 2011/65/EU (RoHS), Railway according to EN 50155 class OT1/ST2, EN 45545 Railway
<b>Order Code</b>		NB3800-2LpWacDa-GVi