

NB2800-2LWacDf-GVi

Fahrzeug-Router mit 2x LTE + WLAN-ac + 2x GbE + 1 TB SSD + GNSS + Virtualisierung + E-Mark

Leistungstarker und modularer Mobilfunk-Router für drahtlosen Internetzugang im Fahrzeug.



Hauptmerkmale

Mobilfunk	2x LTE, UMTS, GSM
SIM	4x Micro SIM
WiFi / WLAN	1x IEEE 802.11a/b/g/n/ac (Wi-Fi 5), 100 Clients im Access Point Mode
Ethernet	2x Gigabit Ethernet
Speisung	12 VDC bis 48 VDC, Zündungserkennung
Erweiterter Speicher	1 TB SSD
Betriebstemperatur	-25 °C bis +70 °C
Software	Routing, Network Services, VPN, Firewall, Link Management, Supervisor, SDK, LXC, freie Updates
Konformität	CE (RED), Fahrzeug (UNECE-R10, UNECE-R118), ITxPT optional
Modularität	Erweiterungen auf Anfrage

Produktbeschreibung

Der NB2800 bietet drahtlosen Internetzugang im Fahrzeug.

Anwendungen

- Blaulichtorganisationen
- Flottenmanagement
- Passagier-Infotainment
- Fahrkartensysteme
- eMobility
- Telematik
- Videoüberwachung
- Intelligenter Verkehr

Spezifikation

Mobile / Cellular	Standard	2x Multimode LTE, UMTS, GSM for EMEA 4G - LTE B1, B3, B7, B8, B20, B28A 3G - DC-HSPA+/UMTS B1 (2100), B3 (1800), B8 (900) 2G - GSM/GPRS/EDGE B3 (1800), B8 (900) Category LTE Cat 4 Antenna ports 2x2 MIMO Data rate down / up (max) 150 Mbps / 50 Mbps Voice CSFB, VoLTE (mit optionaler Software-Lizenz) FCC ID - Region Europe
	Region	Europe
	Connectors	4x FAKRA D-coded male
	SIM	4x Micro SIM - 3FF
WiFi / WLAN	Standard	1x WLAN 2.4/5 GHz a/b/g/n/ac (Wi-Fi 5) Wireless standard IEEE 802.11a/b/g/n/ac (Wi-Fi 5) Frequency 2.4/5 GHz Diversity 2x2 MIMO Data rate (max) 300 Mbps (2.4 GHz) / 866 Mbps (5 GHz) Modes Client or access point (up to 100 clients) FCC ID TK4WLE600VX
	Connector	2x FAKRA I-coded male
Ethernet	Standard	2x Gigabit Ethernet Ethernet standard 1000BASE-T, Auto MDIX Speed 10/100/1000 Mbps
	Connector	2x RJ45

Positioning	Standard	<p>1x Multi-GNSS Receiver BeiDou, Galileo, GLONASS, GPS gpsOne Gen 9 Antennas Active or passive Tracking Sensitivity Up to -160 dBm Services Standalone CEP (Circular Error Probability) < 2m (CEP 50), (Open sky conditions, Horizontal)</p>
	Connector	1x FAKRA C-coded male
USB	Standard	1x USB 3.0 Host
	Connector	1x Type A
Serial, Fieldbus	Protocol	<p>1x RS-232 Protocol EIA-232 Signals TX, RX Signal level High > 5 VDC, low < -5 VDC Bit rate Up to 115 200 Bit/s</p>
	Connector	1x Terminal block header 5 mm
Extended Storage		<p>1 TB SSD Capacity 1 TB Technology SSD Data Application data such as logs, media content, ...</p>
System	Core	1.3 GHz dual core, 1 GB RAM, 4 GB flash
	Module Slots	2x miniPCIe (PCIe + USB), 2x miniPCIe (USB)
Software	Features	<p>NetModule Router Software Package The standard software package includes an intuitive user interface, covering all modern routing protocols and enables efficient mass deployment. General Fail-safe update (FOTA), upgrade via USB, HTTP(S), (S)FTP or TFTP, remote CLI & WebGUI, RADIUS authentication, Simple Certificate Enrollment Protocol (SCEP), Hardware- und Software Watchdog Remote Management Manage and monitor devices with SNMP V1/V2/V3, Netmodule vendor MIB, telnet, SSH, or HTTP/HTTPS Cellular Networking Multi-SIM / eSIM support (optional license), multi-APN support, signal strength monitoring, dedicated bearers, CSFB/VoLTE calls (optional license) Wireless LAN Access Point, Client Mode, Mesh Point or Dual Modes (Mesh Access Point / Access Point - Client), WLAN Pseudo-Bridge Client Mode: Multiple Client SSID Profile, Encryption: Open, WEP, WPA1/2/3-Personal, WPA1/2/3-Enterprise. Fast Roaming: Fast BSS Transition (802.11r), PreAuthentication, Protected Management Frames (802.11w) AP Mode: Multi-SSIDs (up to 8) Encryption: Open WPA1/2/3-Personal, WPA1/2/3-Enterprise Fast Roaming: Fast BSS Transition (802.11r), PreAuthentication, DFS support Protected Management Frames (802.11w) Client Tracking, Band Steering, Hide SSID broadcasting, Isolate Clients, Accounting, Short guard Intervall Mesh Mode (802.11s): Encryption: None, SAE. Gateway announcements Link Management Link prioritization, link aggregation, load balancing, multipath-TCP, IP-passthrough, link supervision, Services DHCP Client/Server, DNS Caching Server, Email, SMS Service, NTP Client/Server, SNTP Server, DynDNS, SSH Server, SNMP Agent, HTTP/HTTPS/FTP Server, IPv6 for WAN, 802.1x over Ethernet, MQTT Broker Voice Gateway (SIP, Call Routing, Audio with optional license) Coovachilli Hotspot Routing Destination, policy, multipath, mobile-IP, OSPF, BGP, multicast, TCP-MSS clamping, bridging discovery protocols LLDAP, CDP, SONMP, EDP, FDP, IRDP, VRRP, STP/RSTP, VRRP, VLAN, PPPoE, VXLAN VPN OpenVPN, IPsec (IKEv1 and IKEv2), PPTP, GRE, L2TP, CSD dial-in, Certificate revocation service Firewall Stateful firewall, connection tracking, NAT, NAPT, masquerading, bridge filtering, Adress translation (based on SRC and DST ports) Encryption supporting password protected PKCS12 files, integrated random certificate key generator, "Let's encrypt" certificate, ECC (Certificates with Elliptic Cryptography) Quality of Service Diffserv, SFQ, HTB, Priority-based Queuing, Netflow (Softflow) Programmability SDK Troubleshooting Logging, Ping, Traceroute, Tcpdump, Speed-test</p>
	Licenses	<p>GNSS/GPS, Services Server with JSON-, NMEA stream LXC virtualization Enabled service Linux Container (LXC) environment to integrate customer specific applications, isolated from the router functionalities</p>
Power	Input Voltage	<p>12, 24, 48 VDC Nominal voltages 12, 24, 48 VDC Absolute voltages 12 VDC to 48 VDC (-25 % / +25 %) Ignition sense Input with delayed shutdown</p>
	Ignition Sense	Ja
	Connector Consumption	<p>1x Terminal block header 5 mm 20 W (max)</p>
Mounting		Bracket
Dimensions	W x H x D	Width 164/190 mm x height 58 mm x depth 139.5 mm

Weight		800 g
Environment	Operating Temperature	-25°C to +70°C
	Ingress Protection Level	IP40
MTBF		170'000 h / 19.4 years, according SN29500 at environmental temperature 40 °C
Lieferumfang		Device, General safety instructions, Terminal block
Certifications	Compliance Domain	CE according to 2014/53/EU (RED), Vehicle according to UNECE-R10, UNECE-R118 Vehicle
Order Code		NB2800-2LWacDf-GVi