

# Antenna-Wall-2L

## Wall Antenna with MIMO LTE or WiFi

Vertical polarization antenna for 4G, 3G, 2G networks



### Keyfeatures

<b>Cellular</b>	MIMO LTE / UMTS / GSM
<b>WiFi</b>	MIMO 2.4 GHz

### Specifications

<b>Mobile / Cellular</b>	<b>Standard</b>	2 x LTE / UMTS / GSM <b>LTE</b> Bands: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 18, 19, 20, 23, 25, 26, 27, 30, 65, 66, 69 - TDD Bands: 33, 34, 35, 36, 37, 38, 39, 40, 41, 53 <b>UMTS</b> Bands: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 19, 20, 25, 26 - TDD Bands: 0, 1, 2, 3, 4, 5, 6, 7 <b>GSM</b> Bands: 810 T-GSM, 850, 900 P, 900 E, 900 R, 1800 DCS, 1900 PCS <b>Frequency</b> 790 - 960, 1710 - 2700
	<b>Specification</b>	<b>Gain</b> 1.6 dBi @ 790 - 960 MHz 4 dBi @ 1710 - 2700 MHz <b>VSWR</b> ≤ 2 typ. <b>Impedance</b> 50 Ohm <b>Radiation</b> omnidirectional
	<b>Connectors</b>	2x SMA male fix connected 5m antenna cable
<b>Mechanical</b>	<b>Dimensions</b>	<b>Diameter</b> 134 mm <b>Height</b> 234 mm
	<b>Weight</b>	620 g
	<b>Mounting</b>	Bracket Window
	<b>Color</b>	RAL9001 cream/grey
<b>Environment</b>	<b>Operating Temperature</b>	-40°C to +70°C
	<b>Ingress Protection Level</b>	IP65
<b>Certifications</b>	<b>Compliance Standards</b>	Safety Complies with UL, CE, EN, CSA and IEC standards UL 94-V0, EN 13823, MIL-STD 810F/ASTM B117
	<b>Domain</b>	Industrial
	<b>Extension Cables</b>	<b>Cellular</b>
<b>Other</b>	<b>Order Code</b>	Antenna-Wall-2L