

Antenna-Wall-2L

Wall Antenna with MIMO LTE or WiFi

Vertical polarization antenna for 4G, 3G, 2G networks



Keyfeatures

Cellular	MIMO LTE / UMTS / GSM
WiFi	MIMO 2.4 GHz

Specifications

Mobile / Cellular	Standard	2 x LTE / UMTS / GSM LTE Bands: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 18, 19, 20, 23, 25, 26, 27, 30, 65, 66, 69 - TDD Bands: 33, 34, 35, 36, 37, 38, 39, 40, 41, 53 UMTS Bands: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 19, 20, 25, 26 - TDD Bands: 0, 1, 2, 3, 4, 5, 6, 7 GSM Bands: 810 T-GSM, 850, 900 P, 900 E, 900 R, 1800 DCS, 1900 PCS Frequency 790 - 960, 1710 - 2700
	Specification	Gain 1.6 dBi @ 790 - 960 MHz 4 dBi @ 1710 - 2700 MHz VSWR ≤ 2 typ. Impedance 50 Ohm Radiation omnidirectional
	Connectors	2x SMA male fix connected 5m antenna cable
Mechanical	Dimensions	Diameter 134 mm Height 234 mm
	Weight	620 g
	Mounting	Bracket Window
	Color	RAL9001 cream/grey
Environment	Operating Temperature	-40°C to +70°C
	Ingress Protection Level	IP65
Certifications	Compliance Standards	Safety Complies with UL, CE, EN, CSA and IEC standards UL 94-V0, EN 13823, MIL-STD 810F/ASTM B117
	Domain	Industrial
	Extension Cables	Cellular
Other	Order Code	Antenna-Wall-2L