

NB2810-2L2Wac-Glx

Vehicle Router with 2x LTE + 2x WLAN-ac + 2x GbE-M12 + GNSS + ITxPT + E-Mark

High-performance and modular mobile router for wireless Internet access in vehicles.



Keyfeatures

| | |
|------------------------------|--|
| Mobile / Cellular | 2x LTE, UMTS, GSM |
| SIM | 4x Micro SIM |
| WiFi / WLAN | 1x Dual-band IEEE 802.11a/b/g/n/ac (Wi-Fi 5), 100 Clients in Access Point Mode |
| Ethernet | 2x Gigabit Ethernet M12 |
| Power | 12 VDC to 48 VDC, Ignition Sense |
| Positioning | Multi-GNSS |
| Operation Temperature | -25 °C to +70 °C |
| Software | Routing, Network Services, VPN, Firewall, Link Management, Supervisor, SDK, free updates |
| Compliance | CE (RED), Vehicle (UNECE-R10, UNECE-R118), ITxPT |
| Modularity | Extensions on request |

Product description

The NB2810 provides in-vehicle wireless Internet access.

Applications

- Fleet Management
- Passenger WiFi
- Passenger Infotainment
- Ticketing
- CCTV

Specifications

| | | |
|--------------------------|-------------------|---|
| Mobile / Cellular | Standard | 2x Multimode LTE, UMTS, GSM for EMEA 4G - LTE B1, B3, B7, B8, B20, B28A 3G - DC-HSPA+/UMTS B1 (2100), B3 (1800), B8 (900) 2G - GSM/GPRS/EDGE B3 (1800), B8 (900) Category LTE Cat 4 Antenna ports 2x2 MIMO Data rate down / up (max) 150 Mbps / 50 Mbps Voice CSFB, VoLTE (with optional Software License) FCC ID - Region Europe |
| | Region | Europe |
| | Connectors | 4x FAKRA D-coded male |
| | SIM | 4x Micro SIM - 3FF |
| WiFi / WLAN | Standard | 2x WLAN 2.4/5 GHz a/b/g/n/ac (Wi-Fi 5) Wireless standard IEEE 802.11a/b/g/n/ac (Wi-Fi 5) Frequency 2.4/5 GHz Diversity 2x2 MIMO Data rate (max) 300 Mbps (2.4 GHz) / 866 Mbps (5 GHz) Modes Client or access point (up to 100 clients) FCC ID TK4WLE600VX |
| | Connector | 4x FAKRA I-coded male |
| Ethernet | Standard | 2x Gigabit Ethernet Ethernet standard 1000BASE-T, Auto MDIX Speed 10/100/1000 Mbps |
| | Connector | 2x M12 X-coded female |

| | | |
|-------------------------|--|--|
| Positioning | Standard | <p>1x Multi-GNSS Receiver BeiDou, Galileo, GLONASS, GPS gpsOne Gen 9 Antennas Active or passive Tracking Sensitivity Up to -160 dBm Services Standalone CEP (Circular Error Probability) < 2m (CEP 50), (Open sky conditions, Horizontal)</p> |
| | Connector | 1x FAKRA C-coded male |
| USB | Standard | 1x USB 3.0 Host |
| | Connector | 1x Type A |
| Serial, Fieldbus | Protocol | <p>1x RS-232 Protocol EIA-232 Signals TX, RX Signal level High > 5 VDC, low < -5 VDC Bit rate Up to 115 200 Bit/s</p> |
| | Connector | 1x Terminal block header 3.5 mm (screw locking) |
| System | Core | 1.3 GHz dual-core, 1 GB RAM, 4 GB flash |
| | Module Slots | 2x miniPCIe (PCIe + USB), 2x miniPCIe (USB) |
| Software | Features | <p>NetModule Router Software (supported features depending on product variant) Package The standard software package includes an intuitive user interface, covering all modern routing protocols and enables efficient mass deployment. General Fail-safe update (FOTA), upgrade via USB, HTTP(S), (S)FTP or TFTP, remote CLI & WebGUI, RADIUS authentication, Simple Certificate Enrollment Protocol (SCEP), Hardware- und Software Watchdog Remote Management Manage and monitor devices with SNMP V1/V2/V3, Netmodule vendor MIB, telnet, SSH, or HTTP/HTTPS Cellular Networking Multi-SIM / eSIM support (optional license), multi-APN support, signal strength monitoring, dedicated bearers, CSFB/VoLTE calls (optional license) Wireless LAN Access Point, Client Mode, Mesh Point or Dual Modes (Mesh Access Point / Access Point - Client), WLAN Pseudo-Bridge Client Mode: Multiple Client SSID Profile, Encryption: Open, WEP, WPA1/2/3-Personal, WPA1/2/3-Enterprise. Fast Roaming: Fast BSS Transition (802.11r), PreAuthentication, Protected Management Frames (802.11w) AP Mode: Multi-SSIDs (up to 8) Encryption: Open WPA1/2/3-Personal, WPA1/2/3-Enterprise Fast Roaming: Fast BSS Transition (802.11r), PreAuthentication, DFS support Protected Management Frames (802.11w) Client Tracking, Band Steering, Hide SSID broadcasting, Isolate Clients, Accounting, Short guard Intervall Mesh Mode (802.11s): Encryption: None, SAE. Gateway announcements Link Management Link prioritization, link aggregation, load balancing, multipath-TCP, IP-passthrough, link supervision, Services DHCP Client/Server, DNS Caching Server, Email, SMS Service, NTP Client/Server, SNTP Server, DynDNS, SSH Server, SNMP Agent, HTTP/HTTPS/FTP Server, IPv6 for WAN, 802.1x over Ethernet, MQTT Broker Voice Gateway (SIP, Call Routing, Audio with optional license) Coovachilli Hotspot Routing Destination, policy, multipath, mobile-IP, OSPF, BGP, multicast, TCP-MSS clamping, bridging discovery protocols LLDP, CDP, SONMP, EDP, FDP, IRDP, VRRP, STP/RSTP, VRRP, VLAN, PPPoE, VXLAN VPN OpenVPN, IPsec (IKEv1 and IKEv2), PPTP, GRE, L2TP, CSD dial-in, Certificate revocation service Firewall Stateful firewall, connection tracking, NAT, NAPT, masquerading, bridge filtering, Adress translation (based on SRC and DST ports) Encryption supporting password protected PKCS12 files, integrated random certificate key generator, "Let's encrypt" certificate, ECC (Certificates with Elliptic Cryptography) Quality of Service Diffserv, SFQ, HTB, Priority-based Queuing, Netflow (Softflow) Programmability SDK Troubleshooting Logging, Ping, Traceroute, Tcpdump, Speed-test</p> |
| | Licenses | <p>GNSS, Enabled service GNSS location service Server with JSON-, NMEA stream ITxPT Enabled services Inventory, Time, FMS2IP (requires -F option), Vehicle2IP (requires -F option), Location (requires -G option) Standard ITxPT software compliance</p> |
| Power | Input Voltage | <p>12, 24, 48 VDC Nominal voltages 12, 24, 48 VDC Absolute voltages 12 VDC to 48 VDC (-25 % / +25 %) Ignition sense Input with delayed shutdown</p> |
| | Ignition Sense | Yes |
| | Connector Consumption | <p>1x Terminal block header 3.5 mm (screw locking) 20 W (max)</p> |
| Mounting | | Bracket |
| Dimensions | W x H x D | Width 164/190 mm x height 58 mm x depth 139.5 mm |
| Weight | | 800 g |

| | | |
|--------------------------|---|--|
| Environment | Operating Temperature Ingress Protection Level | -25°C to +70°C IP40 |
| MTBF | | 200'000 h / 22.8 years, according SN29500 at environmental temperature 40 °C |
| Scope of delivery | | Device, General safety instructions, Terminal block |
| Certifications | Compliance Domain | CE according to 2014/53/EU (RED), Vehicle according to UNECE-R10, UNECE-R118, ITxPT (hardware compliance requires adapter cables) Vehicle |
| Order Code | | NB2810-2L2Wac-Glx |