

NB800-LWWtSu2Cm-G

IIoT Router with LTE + WLAN + BLE + ETH + USB + 2x CAN-passive + GNSS

Compact and modular mobile router to connect remote locations.



Keyfeatures

Mobile / Cellular	1x LTE, UMTS, GSM
SIM	1x Micro SIM / 1x eSIM chip (on request)
WiFi / WLAN	1x Dual-band IEEE 802.11a/b/g/n (Wi-Fi 4), 1x Bluetooth Low Energy
Ethernet	1x Fast Ethernet
Serial / Fieldbus	2x CAN passive (read only)
USB	USB 2.0 Host
Positioning	Multi-GNSS
Operation Temperature	-40 °C to +70 °C
Software	Routing, Network Services, VPN, Firewall, Link Management, Supervisor, SDK, free updates
Compliance	CE (RED), UKCA (RER), UL/IEC/EN 62368-1, FCC,
Modularity	Extensions on request

Product description

The compact NB800 is the cost-effective solution for a robust Internet connection in an industrial environment.

Applications

- Condition Monitoring
- Industrial Security
- Factory Automation
- Remote Management
- Environmental Monitoring
- Intelligent Lighting Management
- Smart Buildings

Specifications

Mobile / Cellular	Standard	1x Multimode LTE, UMTS, GSM for EMEA 4G - LTE B1 (2100), B3 (1800), B5 (850), B7 (2600), B8 (900), B20 (800) 3G - DC-HSPA+/UMTS B1 (2100), B2 (1900), B5 (850), B8 (900) 2G - GSM/GPRS/EDGE B2 (1900), B3 (1800), B5 (850), B8 (900) Category LTE Cat 4 Antenna ports 2x2 MIMO Data rate down / up (max) 150 Mbps / 50 Mbps Voice CSFB (with optional Software License) FCC ID XPYTOBYL210
	Region	Europe
	Connectors	2x SMA female
	SIM	1x Micro SIM - 3FF / eSIM Chip (on request)
WiFi / WLAN	Standard	1x Dual-band WLAN 2.4/5 GHz a/b/g/n (Wi-Fi 4) + BT 4.2 combo Wireless standard IEEE 802.11a/b/g/n (Wi-Fi 4) Bluetooth 4.2, Bluetooth Low Energy Frequency 2.4/5 GHz Antenna ports 2x2 MIMO Data rate (max) 144 Mbps 2.4 GHz 2x2 MIMO, 150 Mbps 5 GHz SISO Modes Client or access point (up to 10 clients) FCC ID POR-WL18DBMOD
	Connector	2x SMA female
Ethernet	Standard	1x Fast Ethernet Ethernet standard 100BASE-TX, Auto MDIX Speed 10/100 Mbps
	Connector	1x RJ45

Positioning	Standard	<p>1x Multi-GNSS Receiver BeiDou, Galileo, GLONASS, GPS/QZSS 72-channel u-blox M8 engine 3 concurrent GNSS channels Antennas Active or passive Accuracy Up to 2.5 m CEP Sensitivity Up to -167 dBm Services Standalone, Assisted GPS Data server with JSON, NMEA data stream</p>
	Connector	1x SMA female
USB	Standard	1x USB 2.0 Host
	Connector	1x Type A
Serial, Fieldbus	Protocol	<p>2x CAN Protocol Controller Area Network V2.0B (ISO 11898) Signals CANH, CANL Signal level High > 2.75 V, low < 2.0 V Bit rate Up to 1 Mbps Termination No internal bus termination Bus access Passive - read access only Module CAN shield</p>
	Connector	1x Terminal block header 3.5 mm
System	Core	1 GHz single core, 512 MB RAM, 4 GB flash, HW Rev. B02
	Module Slots	1x Shield
Software	Features	<p>NetModule Router Software (supported features depending on product variant) Package The standard software package includes an intuitive user interface, covering all modern routing protocols and enables efficient mass deployment. General Fail-safe update (FOTA), upgrade via USB, HTTP(S), (S)FTP or TFTP, remote CLI & WebGUI, RADIUS authentication, Simple Certificate Enrollment Protocol (SCEP), Hardware- und Software Watchdog Remote Management Manage and monitor devices with SNMP V1/V2/V3, Netmodule vendor MIB, telnet, SSH, or HTTP/HTTPS Cellular Networking Multi-SIM / eSIM support (optional license), multi-APN support, signal strength monitoring, dedicated bearers, CSFB/VoLTE calls (optional license) Wireless LAN Access Point, Client Mode, Mesh Point or Dual Modes (Mesh Access Point / Access Point - Client), WLAN Pseudo-Bridge Client Mode: Multiple Client SSID Profile, Encryption: Open, WEP, WPA1/2/3-Personal, WPA1/2/3-Enterprise. Fast Roaming: Fast BSS Transition (802.11r), PreAuthentication, Protected Management Frames (802.11w) AP Mode: Multi-SSIDs (up to 8) Encryption: Open WPA1/2/3-Personal, WPA1/2/3-Enterprise Fast Roaming: Fast BSS Transition (802.11r), PreAuthentication, DFS support Protected Management Frames (802.11w) Client Tracking, Band Steering, Hide SSID broadcasting, Isolate Clients, Accounting, Short guard Intervall Mesh Mode (802.11s): Encryption: None, SAE. Gateway announcements Link Management Link prioritization, link aggregation, load balancing, multipath-TCP, IP-passthrough, link supervision, Services DHCP Client/Server, DNS Caching Server, Email, SMS Service, NTP Client/Server, SNTP Server, DynDNS, SSH Server, SNMP Agent, HTTP/HTTPS/FTP Server, IPv6 for WAN, 802.1x over Ethernet, MQTT Broker Voice Gateway (SIP, Call Routing, Audio with optional license) Coovachilli Hotspot Routing Destination, policy, multipath, mobile-IP, OSPF, BGP, multicast, TCP-MSS clamping, bridging discovery protocols LLDP, CDP, SONMP, EDP, FDP, IRDP, VRRP, STP/RSTP, VRRP, VLAN, PPPoE, VXLAN VPN OpenVPN, IPsec (IKEv1 and IKEv2), PPTP, GRE, L2TP, CSD dial-in, Certificate revocation service Firewall Stateful firewall, connection tracking, NAT, NAPT, masquerading, bridge filtering, Adress translation (based on SRC and DST ports) Encryption supporting password protected PKCS12 files, integrated random certificate key generator, "Let's encrypt" certificate, ECC (Certificates with Elliptic Cryptography) Quality of Service Diffserv, SFQ, HTB, Priority-based Queuing, Netflow (Softflow) Programmability SDK Troubleshooting Logging, Ping, Traceroute, Tcpdump, Speed-test</p>
	Licenses	<p>GNSS Enabled service GNSS location service Server with JSON-, NMEA stream</p>
Power	Input Voltage	<p>12, 24 VDC Nominal voltages 12, 24 VDC Absolute voltages 12 VDC to 24 VDC (-20 % / +20 %)</p>
	Connector	1x Terminal block header 3.5 mm
	Consumption	5 W (average), 10 W (max)
Mounting		Bracket
Dimensions	W x H x D	Width 85/111 mm x height 32 mm x depth 110 mm
Weight		220 g

Environment	Operating Temperature Ingress Protection Level	-40°C to +70°C IP40
MTBF		340'000 h / 38.8 years, according SN29500 at environmental temperature 40 °C
Certifications	Compliance Domain	CE according to 2014/53/EU (RED), 2011/65/EU (RoHS) Industrial
Order Code		NB800-LWWtSu2Cm-G
