

NB3800-N2L-G

Railway Router with 1x 5G + 2x LTE + 5x ETH + GNSS + EN50155

With excellent 5G mobile radio technology for wireless internet access in the vehicle incl. 5-port Ethernet switch.



Keyfeatures

Mobile / Cellular	1x 5G-NR, LTE-A Pro, UMTS 2x LTE, UMTS, GSM
SIM	4x Mini SIM
Ethernet	2x Gigabit Ethernet, 3x Fast Ethernet
Power	24 VDC to 48 VDC
Positioning	Multi-GNSS
Temperature Range	-40 °C to +70 °C, EN 50155 class OT4/ST0
Software	Routing, Network Services, VPN, Firewall, Link Management, Supervisor, SDK, free updates
Compliance	CE (RED), Railway (EN50155, EN45545), ITxPT optional
Modularity	Extensions on request

Product description

The powerful NB3800 with its features, railway approvals and interfaces to on-board electronics, is ideal for applications like passenger WiFi, passenger information systems or video surveillance.

Applications

- Fleet Management
- Mining
- Passenger Infotainment
- Ticketing
- CCTV
- Telematics

Specifications

Mobile / Cellular	Standard	<p>1x Multimode 5G-NR, LTE-A Pro, UMTS</p> <p>5G - NR n1, n2, n3, n5, n7, n8, n12*, n20, n25, n28, n38, n40, n41, n48, n66, n71, n77, n78, n79</p> <p>2014/53/EU (RED): n1, n3, n7, n8, n20, n28, n38, n40, n77, n78</p> <p>4G - LTE-A Pro B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B29DL, B30, B32, B34, B38, B39, B40, B41, B42, B43*, B46(LAA), B48(CRS), B66, B71</p> <p>2014/53/EU (RED): B1, B3, B7, B8, B20, B28, B38, B40</p> <p>3G - DC-HSPA+/UMTS B1, B2, B3, B4, B5, B6, B8, B9, B19</p> <p>2014/53/EU (RED): B1 (2100), B3 (1800), B8 (900)</p> <p>5G NR Modes Sub-6 FDD and TDD</p> <p>LTE Category Cat. 20 up to 7CA</p> <p>MIMO 4x4 MIMO in 5G-NR support on n1, n2 n3, n7, n25, n38, n40, n41, n48, n66, n77, n78, n79 and LTE B1, B2, B3, B4, B7, B25, B30, B38, B39, B40, B41, B42, B43, B46, B48, B66</p> <p>Antenna ports 4</p> <p>Power Class 23dBm (Power Class 3)</p> <p>Data rate down / up (max) up to 5.5 Gbps DL / 2.7 Gbps UL</p> <p>Operation Mode 5G Core SA and NSA operations</p> <p>3GPP 4G/5G Rel. 15, 3G HSPA+ Rel. 18</p> <p>FCC ID RI7FN980</p> <p>Voice -</p> <p>Region Europe, Middle East and Africa (EMEA), North America (NA), Asia and Pacific (APAC)</p> <p>* future Module Firmware release</p> <p>2x Multimode LTE, UMTS, GSM for EMEA</p> <p>4G - LTE B1, B3, B7, B8, B20, B28A</p> <p>3G - DC-HSPA+ /UMTS B1 (2100), B3 (1800), B8 (900)</p> <p>2G - GSM/GPRS/EDGE B3 (1800), B8 (900)</p> <p>Category LTE Cat 4</p> <p>Antenna ports 2x2 MIMO</p> <p>Data rate down / up (max) 150 Mbps / 50 Mbps</p> <p>Voice CSFB, VoLTE (with optional Software License)</p> <p>FCC ID -</p> <p>Region Europe</p>
	Region Connectors SIM	<p>Europe</p> <p>8x TNC female</p> <p>4x Mini SIM - 2FF</p>
Ethernet	Standard	<p>2x Gigabit Ethernet</p> <p>Ethernet standard 1000BASE-T, Auto MDIX</p> <p>Speed 10/100/1000 Mbps</p> <p>3x Fast Ethernet</p> <p>Ethernet standard 100BASE-TX, Auto MDIX</p> <p>Speed 10/100 Mbps</p>
	Connector	2x M12 X-coded female, 3x M12 D-coded female
Positioning	Standard	<p>1x Multi-GNSS</p> <p>Receiver BeiDou, Galileo, GLONASS, GPS</p> <p>gpsOne Gen 9</p> <p>Antennas Active or passive</p> <p>Sensitivity Up to -161 dBm</p> <p>CEP (Circular Error Probability) <2m (Open sky conditions. Standalone)</p> <p>Min Update Rate 1Hz</p> <p>Services Standalone</p>
	Connector	1x TNC female
USB	Standard	1x USB 2.0 Host
	Connector	1x Type A
Serial, Fieldbus	Protocol	<p>1x RS-232</p> <p>Protocol EIA-232</p> <p>Signals TX, RX</p> <p>Signal level High > 5 VDC, low < -5 VDC</p> <p>Bit rate Up to 115 200 Bit/s</p>
	Connector	1x M12 A-coded female
System	Core	1.3 GHz dual-core, 1 GB RAM, 4 GB flash
	Module Slots	2x miniPCIe (PCIe + USB), 4x miniPCIe (USB)

Software	Features	<p>NetModule Router Software (supported features depending on product variant)</p> <p>Package The standard software package includes an intuitive user interface, covering all modern routing protocols and enables efficient mass deployment.</p> <p>General Fail-safe update (FOTA), upgrade via USB, HTTP(S), (S)FTP or TFTP, remote CLI & WebGUI, RADIUS authentication, Simple Certificate Enrollment Protocol (SCEP), Hardware- und Software Watchdog</p> <p>Remote Management Manage and monitor devices with SNMP V1/V2/V3, Netmodule vendor MIB, telnet, SSH, or HTTP/HTTPS</p> <p>Cellular Networking Multi-SIM / eSIM support (optional license), multi-APN support, signal strength monitoring, dedicated bearers, CSFB/VoLTE calls (optional license)</p> <p>Wireless LAN Access Point, Client Mode, Mesh Point or Dual Modes (Mesh Access Point / Access Point - Client), WLAN Pseudo-Bridge Client Mode: Multiple Client SSID Profile, Encryption: Open, WEP, WPA1/2/3-Personal, WPA1/2/3-Enterprise. Fast Roaming: Fast BSS Transition (802.11r), PreAuthentication, Protected Management Frames (802.11w) AP Mode: Multi-SSIDs (up to 8) Encryption: Open WPA1/2/3-Personal, WPA1/2/3-Enterprise Fast Roaming: Fast BSS Transition (802.11r), PreAuthentication, DFS support Protected Management Frames (802.11w) Client Tracking, Band Steering, Hide SSID broadcasting, Isolate Clients, Accounting, Short guard Intervall Mesh Mode (802.11s): Encryption: None, SAE. Gateway announcements</p> <p>Link Management Link prioritization, link aggregation, load balancing, multipath-TCP, IP-passthrough, link supervision,</p> <p>Services DHCP Client/Server, DNS Caching Server, Email, SMS Service, NTP Client/Server, SNMP Server, DynDNS, SSH Server, SNMP Agent, HTTP/HTTPS/FTP Server, IPv6 for WAN, 802.1x over Ethernet, MQTT Broker Voice Gateway (SIP, Call Routing, Audio with optional license) Coovachilli Hotspot</p> <p>Routing Destination, policy, multipath, mobile-IP, OSPF, BGP, multicast, TCP-MSS clamping, bridging discovery protocols LLDAP, CDP, SONMP, EDP, FDP, IRDP, VRRP, STP/RSTP, VRRP, VLAN, PPPoE, VXLAN</p> <p>VPN OpenVPN, IPsec (IKEv1 and IKEv2), PPTP, GRE, L2TP, CSD dial-in, Certificate revocation service</p> <p>Firewall Stateful firewall, connection tracking, NAT, NAPT, masquerading, bridge filtering, Adress translation (based on SRC and DST ports)</p> <p>Encryption supporting password protected PKCS12 files, integrated random certificate key generator, "Let's encrypt" certificate, ECC (Certificates with Elliptic Cryptography)</p> <p>Quality of Service Diffserv, SFQ, HTB, Priority-based Queuing, Netflow (Softflow)</p> <p>Programmability SDK</p> <p>Troubleshooting Logging, Ping, Traceroute, Tcpdump, Speed-test</p>
	Licenses	<p>GNSS</p> <p>Enabled service GNSS location service Server with JSON-, NMEA stream</p>
Power	Input Voltage	<p>24, 48 VDC</p> <p>Nominal voltages 24, 48 VDC</p> <p>Absolute voltages 24 VDC to 48 VDC (-30 % / +30 %)</p> <p>Galvanic isolation 1500 VDC</p> <p>Standard EN 50155 class S2/C1</p>
	Connector Consumption	<p>1x M12 A-coded male</p> <p>25 W (max)</p>
Dimensions	W x H x D	Width 167/190 mm x height 121.1 mm x depth 106.5 mm
Weight		1800 g
Environment	Operating Temperature	-40°C to +70°C
	Ingress Protection Level	IP40
MTBF		150'000 h / 17.1 years, according SN29500 at environmental temperature 40 °C
Certifications	Compliance Domain	CE according to 2014/53/EU (RED), 2011/65/EU (RoHS), Railway according to EN 50155 class OT4/ST0, EN 45545 Railway
Order Code		NB3800-N2L-G