

NB2800-2Wac

Vehicle Router with 2x WLAN-ac + 2x GbE + E-Mark

High-performance and modular mobile router for wireless Internet access in vehicles.



Keyfeatures

WiFi / WLAN	1x Dual-band IEEE 802.11a/b/g/n/ac (Wi-Fi 5), 100 Clients in Access Point Mode
Ethernet	2x Gigabit Ethernet
Power	12 VDC to 48 VDC, Ignition Sense
Operation Temperature	-25 °C to +70 °C
Software	Routing, Network Services, VPN, Firewall, Link Management, Supervisor, SDK, free updates
Compliance	CE (RED), Vehicle (UNECE-R10, UNECE-R118), ITxPT optional
Modularity	Extensions on request

Product description

The NB2800 provides in-vehicle wireless Internet access.

Applications

- Passenger WiFi
- Passenger Infotainment

Specifications

Mobile / Cellular	Region	United States of America (USA)
WiFi / WLAN	Standard	2x WLAN 2.4/5 GHz a/b/g/n/ac (Wi-Fi 5) Wireless standard IEEE 802.11a/b/g/n/ac (Wi-Fi 5) Frequency 2.4/5 GHz Diversity 2x2 MIMO Data rate (max) 300 Mbps (2.4 GHz) / 866 Mbps (5 GHz) Modes Client or access point (up to 100 clients) FCC ID TK4WLE600VX
	Connector	4x SMA female
Ethernet	Standard	2x Gigabit Ethernet Ethernet standard 1000BASE-T, Auto MDIX Speed 10/100/1000 Mbps
	Connector	2x RJ45
USB	Standard	1x USB 3.0 Host
	Connector	1x Type A
Serial, Fieldbus	Protocol	1x RS-232 Protocol EIA-232 Signals TX, RX Signal level High > 5 VDC, low < -5 VDC Bit rate Up to 115 200 Bit/s
	Connector	1x Terminal block header 5 mm
System	Core	1.3 GHz dual-core, 1 GB RAM, 4 GB flash
	Module Slots	2x miniPCIe (PCIe + USB), 2x miniPCIe (USB)

Software	Features	<p>NetModule Router Software (supported features depending on product variant)</p> <p>Package The standard software package includes an intuitive user interface, covering all modern routing protocols and enables efficient mass deployment.</p> <p>General Fail-safe update (FOTA), upgrade via USB, HTTP(S), (S)FTP or TFTP, remote CLI & WebGUI, RADIUS authentication, Simple Certificate Enrollment Protocol (SCEP), Hardware- und Software Watchdog</p> <p>Remote Management Manage and monitor devices with SNMP V1/V2/V3, Netmodule vendor MIB, telnet, SSH, or HTTP/HTTPS</p> <p>Cellular Networking Multi-SIM / eSIM support (optional license), multi-APN support, signal strength monitoring, dedicated bearers, CSFB/VoLTE calls (optional license)</p> <p>Wireless LAN Access Point, Client Mode, Mesh Point or Dual Modes (Mesh Access Point / Access Point - Client), WLAN Pseudo-Bridge Client Mode: Multiple Client SSID Profile, Encryption: Open, WEP, WPA1/2/3-Personal, WPA1/2/3-Enterprise. Fast Roaming: Fast BSS Transition (802.11r), PreAuthentication, Protected Management Frames (802.11w) AP Mode: Multi-SSIDs (up to 8) Encryption: Open WPA1/2/3-Personal, WPA1/2/3-Enterprise Fast Roaming: Fast BSS Transition (802.11r), PreAuthentication, DFS support Protected Management Frames (802.11w) Client Tracking, Band Steering, Hide SSID broadcasting, Isolate Clients, Accounting, Short guard Intervall Mesh Mode (802.11s): Encryption: None, SAE. Gateway announcements</p> <p>Link Management Link prioritization, link aggregation, load balancing, multipath-TCP, IP-passthrough, link supervision,</p> <p>Services DHCP Client/Server, DNS Caching Server, Email, SMS Service, NTP Client/Server, SNTP Server, DynDNS, SSH Server, SNMP Agent, HTTP/HTTPS/FTP Server, IPv6 for WAN, 802.1x over Ethernet, MQTT Broker Voice Gateway (SIP, Call Routing, Audio with optional license) Coovachilli Hotspot</p> <p>Routing Destination, policy, multipath, mobile-IP, OSPF, BGP, multicast, TCP-MSS clamping, bridging discovery protocols LLDAP, CDP, SONMP, EDP, FDP, IRDP, VRRP, STP/RSTP, VRRP, VLAN, PPPoE, VXLAN</p> <p>VPN OpenVPN, IPsec (IKEv1 and IKEv2), PPTP, GRE, L2TP, CSD dial-in, Certificate revocation service</p> <p>Firewall Stateful firewall, connection tracking, NAT, NAPT, masquerading, bridge filtering, Adress translation (based on SRC and DST ports)</p> <p>Encryption supporting password protected PKCS12 files, integrated random certificate key generator, "Let's encrypt" certificate, ECC (Certificates with Elliptic Cryptography)</p> <p>Quality of Service Diffserv, SFQ, HTB, Priority-based Queuing, Netflow (Softflow)</p> <p>Programmability SDK</p> <p>Troubleshooting Logging, Ping, Traceroute, Tcpdump, Speed-test</p>
Power	<p>Input Voltage</p> <p>Ignition Sense</p> <p>Connector</p> <p>Consumption</p>	<p>12, 24, 48 VDC</p> <p>Nominal voltages 12, 24, 48 VDC</p> <p>Absolute voltages 12 VDC to 48 VDC (-25 % / +25 %)</p> <p>Ignition sense Input with delayed shutdown</p> <p>Yes</p> <p>1x Terminal block header 5 mm</p> <p>20 W (max)</p>
Mounting		Bracket
Dimensions	W x H x D	Width 164/190 mm x height 58 mm x depth 139.5 mm
Weight		800 g
Environment	<p>Operating Temperature</p> <p>Ingress Protection Level</p>	<p>-25°C to +70°C</p> <p>IP40</p>
MTBF		230'000 h / 26.3 years, according SN29500 at environmental temperature 40 °C
Scope of delivery		Device, General safety instructions, Terminal block
Certifications	Compliance Domain	CE according to 2014/53/EU (RED), Vehicle according to UNECE-R10, UNECE-R118 Vehicle
Order Code		NB2800-2Wac